

correa

correa | XPERTA BED-TYPE



ENVIRONMENTAL PRODUCT DECLARATION (EPD)

Primera fresadora en obtener el certificado EPD

First Milling Machine to obtain EPD certificate

La prima fresatrice che ottiene il certificato EPD

Die erste Fräsmaschine mit Umweltproduktdeklaration EPD

La première fraiseuse qui obtient le certificat EPD



correa | NORMA BED-TYPE



Mesa Table
Tavola - Tisch - Table

Recorridos Traverses
Corse - Bewegungen - Courses

Avances Feeds
Avanzamenti - Vorschübe
Avances

Mandrino vertical
Vertical spindle

Mandrino verticale
Vertikal spindel
Broche verticale

***Peso Weigth**
Peso - Gewichte - Poid

* Sin ATC ni Evacuadores

		XPERTA 20	XPERTA 25	XPERTA 35	XPERTA 45
Superficie Surface Superficie - Oberfläche - Surface	mm	2.300 x 1.000	2.800 x 1.000	3.800 x 1.000	4.800 x 1.000
Peso adm. en mesa Max. load on table Max. peso sulla tavola - Zulässige tischbelastung - Max. poid sur la table	kg	4.500	6.500	9.000	10.500
Longitudinal Longitudinal Longitudinale - Längs - Longitudinale	mm	2.000	2.500	3.500	4.500
Transversal Cross Trasversale - Quer - Transversale	mm		1.000		
Vertical Vertical Verticale - Vertikal - Verticale	mm		1.000		
Rápidos Rapid traverses Avanzamento rapido - Eilgâng - Avances rapides	X Y Z m/min			20	
Cabeza mandrino Spindle nose Cono mandrino - Aufnahme - Nez de la broche				ISO - 50	
Velocidad prog. Programmable speed Velocità programmabile - Drehzahlbereich - Vitesses programmables	r.p.m.			4.000	
Potencia máxima Maximum power Potenza massima - Max. leistung - Puissance maximum	kw			22	
Par máximo Maximum torque Coppia massima - Max. Drehmoment - Couple maximum	Nm			286 - 840	
De la máquina Machine weight Della macchina - Maschinengewicht - De la machine	kg	15.200	16.400	18.600	22.400

correa | NORMA

BED-TYPE

Mesa Table
Tavola - Tisch - Table

Recorridos Traverses
Corse - Bewegungen - Courses

Avances Feeds
Avanzamenti - Vorschübe
Avances

Mandrino vertical
Vertical spindle

Mandrino verticale
Vertikal spindel
Broche verticale

***Peso Weigth**
Peso - Gewichte - Poid

		NORMA 20	NORMA 25	NORMA 35	NORMA 45
Superficie Surface Superficie - Oberfläche - Surface	mm	2.300 x 1.000	2.800 x 1.000	3.800 x 1.000	4.800 x 1.000
Peso adm. en mesa Max. load on table Max. peso sulla tavola - Zulässige tischbelastung - Max. poid sur la table	kg	4.500	6.500	9.000	10.500
Longitudinal Longitudinal Longitudinale - Längs - Longitudinale	mm	2.000	2.500	3.500	4.500
Transversal Cross Trasversale - Quer - Transversale	mm		1.250		
Vertical Vertical Verticale - Vertikal - Verticale	mm		1.500		
Rápidos Rapid traverses Avanzamento rapido - Eilgâng - Avances rapides	X Y Z m/min			20	
Cabeza mandrino Spindle nose Cono mandrino - Aufnahme - Nez de la broche				ISO - 50	
Velocidad prog. Programmable speed Velocità programmabile - Drehzahlbereich - Vitesses programmables	r.p.m.			4.000 , 6.000	
Potencia máxima Maximum power Potenza massima - Max. leistung - Puissance maximum	kw			22	
Par máximo Maximum torque Coppia massima - Max. Drehmoment - Couple maximum	Nm			840	
De la máquina Machine weight Della macchina - Maschinengewicht - De la machine	kg	17.800	19.000	21.200	25.000

* Sin ATC ni Evacuadores